



HF/50MHz TRANSCEIVER

IC-7200



Simple & Tough with IF DSP



* The above photo includes optional MB-116 handles.

Simple & Tough with IF DSP




| IF DSP

The latest IF DSP technology is employed in the IC-7200. While the IC-7200 is an entry-class transceiver, advanced digital features are comparable to higher class transceivers.

| AGC loop management

Distortion and blocking from strong nearby signals are prevented by placing DSP functions inside the AGC loop. The AGC time constants are selectable from fast, slow and off for each operating mode.



| Digital IF filter

Optional filters will be never required for the IC-7200. The built-in digital filter allows you to flexibly select the filter width and shape from soft and sharp* and provides cutting-edge filter characteristics.

* Filter shape is selectable for SSB and CW modes only.

Mode	Passband width range
SSB	50–500Hz; 50Hz step 600Hz–3.6kHz; 100Hz step
CW	50–500Hz; 50Hz step 600Hz–3.6kHz; 100Hz step
RTTY	50–500Hz; 50Hz step 600Hz–2.7kHz; 100Hz step
AM	200Hz–8kHz; 200Hz step

| Digital Twin PBT

Only Icom brings you Twin Passband tuning! Tailor your IF passband with the Twin PBT by electronically shifting the upper and lower edges of the IF filter. Depending on the use of the concentric knobs, you can either narrow the IF passband, or shift the entire passband to eliminate interfering signals.

| Manual notch filter

The manual notch filter delivers more than 70dB of attenuation. Strong interfering tones will be eliminated without adversely affecting the AGC loop performance. On the bottom right of the front panel, a dedicated control knob adjusts the notch filter frequency.

| Digital noise reduction

The digital noise reduction reduces background noise and improves the signal-to-noise ratio. The noise reduction level is adjustable in 16 steps. It improves the readability of voice and data signals.

| Digital noise blanker

The noise blanker reduces pulse-type noise such as engine ignition and sparking. The NB level and width (blanking duration) are adjustable in 100 steps.

| High stability transmitter

The DDS (Direct Digital Synthesizer) creates a clear, clean transmit signal and improves the C/N ratio. With a dual-fan cooling system, the IC-7200 provides stable high quality output even during high duty cycle operation.





HF/50MHz TRANSCEIVER

IC-7200

USB port for PC control

The IC-7200 can be controlled by a PC through a USB port using the CI-V data format. In addition, modulator and received audio can also be transferred over the USB cable. By using appropriate external software, you can record incoming calls and/or transmit preprogrammed messages from your PC.

RF speech compressor

The digital RF speech compressor increases your average talk power in SSB mode. Even when the compression level is increased, the DSP controlled RF speech compressor provides low distortion audio.

CW mode operation

Full break-in, selectable CW carrier point (USB or LSB) and adjustable CW pitch are also standard.

Tough construction against water intrusion

Waterproof protection technologies that are used in Icom's marine radios are applied to

the buttons and knobs on the front panel to provide a measure of protection against water intrusion.

* IC-7200 is NOT waterproof.



Rugged design for outdoor use

The rugged design of the IC-7200 means your enjoyment of this rig is not limited to your shack only.

Other features

- RIT • VOX
- ± 0.5 ppm frequency stability
- LCD backlight (Hi/Lo/Off)
- CI-V interface
- 201 memory channels
- Built-in 20dB attenuator
- Preamplifier • Dial lock
- Auto TS function • 1Hz step tuning
- Band stacking register
- Built-in voice synthesizer • Quick split
- Front facing speaker • Quick set mode

"Rear bumper"

The "rear bumper" protects various connectors on the rear panel and lets you stand the radio on its rear end when the antenna is disconnected, such as while moving or packing the radio.



IC-7200

SPECIFICATIONS

GENERAL

• Frequency range*1 :
 Rx 0.030-60.000000MHz*2
 Tx 1.800- 1.999999MHz 3.500- 3.999999MHz
 5.3305, 5.3465, 5.3665, 5.3715, 5.4035MHz*3
 7.000- 7.300000MHz 10.100-10.150000MHz
 14.000-14.350000MHz 18.068-18.168000MHz
 21.000-21.450000MHz 24.890-24.990000MHz
 28.000-29.700000MHz 50.000-54.000000MHz

*1 Shows USA version. Frequency coverage depends on version.
 *2 Guaranteed range: 0.5-29.999 and 50-54.000 MHz. *3 USB only.

• Mode : USB, LSB, CW, RTTY (FSK), AM
 • No. of memory Ch. : 201Ch. (199 regular, 2 scan edges)
 • Frequency resolution : 1 Hz
 • Frequency stability : Less than ±0.5ppm
 • Power supply requirement : 13.8V DC ±15% (negative ground)
 • Current drain :
 Transmit Max. power 22.0A
 Receive Max. audio 2.0A
 Stand-by 1.3A
 • Operating temp. range : -10°C to +60°C; +14°F to +140°F
 • Antenna connector : SO-239 (506)
 • Dimensions : 241x84x281 mm
 (projections not included) 9 1/2x3 5/16x11 1/16 in
 • Weight (approx.) : 5.5 kg; 12.1 lb

TRANSMITTER

Modulation system :
 SSB Digital PSN modulation
 AM Digital Low power modulation
 • Output power :
 SSB, CW, RTTY 2-100 W
 AM 1-40 W
 • Spurious emissions (Unwanted emission) :
 HF bands Less than -50dB
 50MHz band Less than -63dB
 • Carrier suppression : More than 50dB
 • Unwanted sideband : More than 50dB
 • Microphone connector : 8-pin connector (6006)

RECEIVER

• Intermediate frequencies : 64.455MHz, 455kHz, 15.625kHz
 • Sensitivity (10dB S/N, Preamp ON, Filter shape sharp) :
 SSB, CW Less than 0.16µV (1.8-29.995MHz)
 Less than 0.13µV (50MHz band)
 AM Less than 13µV (0.5-1.8MHz)
 Less than 2µV (1.8-29.995MHz)
 Less than 1µV (50MHz band)

• Squelch sensitivity (SSB, threshold, Preamp ON) :
 Less than 5.6 µV

• Selectivity
 SSB More than 2.4kHz/-6dB
 (BW: 2.4kHz, sharp) Less than 3.6kHz/-60dB
 CW More than 500Hz/-6dB
 (BW: 500Hz, sharp) Less than 900Hz/-60dB
 RTTY (BW: 350Hz) More than 360Hz/-6dB
 Less than 650Hz/-60dB
 AM (BW: 6kHz) More than 6.0kHz/-6dB
 Less than 15.0kHz/-60dB
 • Spurious and image rejection ratio : More than 70dB
 (Except 1/2 IF through on 50MHz band)
 • Audio output power (at 13.8 V DC) : More than 2.0W at 10% distortion with an 8Ω load
 • RIT variable range : ±9.99kHz
 • EXT SP connector : 2-conductor 3.5 (d) mm (1/8") /86

Supplied accessories:

• Hand microphone • DC power cable • Spare fuses

All stated specifications are subject to change without notice or obligations.

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.



IC-PW1/IC-PW1EURO
 HF+50 MHz 1 kW
 HF LINEAR AMPLIFIER
 Covers all HF and 50 MHz bands, provides clean, stable 1 kW output. Automatic antenna tuner and compact detachable controller are standard. 2 exciter inputs are available. (An optional OPC-599 is required.)




AH-2b ANTENNA ELEMENT
 For mobile operation with the AH-4. All bands between 7-30 MHz can be matched.



AH-4 HF+50 MHz AUTOMATIC ANTENNA TUNER
 Covers 3.5-30 MHz with a 7 m (23 ft) or longer wire antenna.



AT-180 AUTOMATIC ANTENNA TUNER
 Compact, light weight antenna tuner.



AH-710 FOLDED DIPOLE ANTENNA
 Covers from 1.9 to 30MHz. Has a PL-259 connector. Easy to assemble (non-kink construction).



SP-20 EXTERNAL SPEAKER
 4 audio filters; headphone jack; can connect to 2 transceivers. Input impedance: 8Ω Max. input power: 5W



SP-21 EXTERNAL SPEAKER
 Input impedance: 8Ω Max. input power: 5W



SP-10 EXTERNAL SPEAKER
 Compact size speaker.



SM-20 DESKTOP MICROPHONE
 High quality desktop microphone. Includes [UP]/[DOWN] switches and low cut function.



HM-36 HAND MICROPHONE
 Same as that supplied with the radio.



CT-17 CI-V LEVEL CONVERTER
 For remote transceiver control from a PC equipped with an RS-232C port.



MB-116 HANDLES
 Protect buttons and knobs on the front panel when moving the radio.



MB-117 CARRYING HANDLE
 Convenient when carrying the transceiver.



MB-118 MOBILE MOUNTING BRACKET
 For mounting the radio in a vehicle.



OPC-599 CABLE ADAPTER
 Converts 13-pin ACC connector to 7-pin + 8-pin ACC connector for connection with IC-PW1/EURO.

PS-300 GENERAL PURPOSE POWER SUPPLY

• Max. 30A output (25A continuous)
 • 9-15V variable output voltage
 • Transformer type
 • Voltage and current meters
 • 209(W)x120(H)x280(D) mm;
 8 7/16 x 4 7/8 x 11 1/2 in dimensions
 (Not available in some countries)

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
 Bellevue, WA 98004, U.S.A.
 Phone: +1 (425) 454-8155
 Fax: +1 (425) 454-1509
 E-mail: sales@icomamerica.com
 URL: <http://www.icomamerica.com>

Icom Canada

Glenwood Centre #150-6165 Highway 17,
 Delta, B.C., V4K 5B8, Canada
 Phone: +1 (604) 952-4266
 Fax: +1 (604) 952-0090
 E-mail: info@icomcanada.com
 URL: <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
 Clayton, VIC 3168 Australia
 Phone: +61 (03) 9549 7500
 Fax: +61 (03) 9549 7505
 E-mail: sales@icom.net.au
 URL: <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki,
 Auckland, New Zealand
 Phone: +64 (09) 274 4062
 Fax: +64 (09) 274 4708
 E-mail: inquiries@icom.co.nz
 URL: <http://www.icom.co.nz>

Icom (Europe) GmbH

Communication Equipment
 Himmelgeister Str. 100,
 D-40225 Düsseldorf, Germany
 Phone: +49 (0211) 346047
 Fax: +49 (0211) 333639
 E-mail: info@icom-europe.com
 URL: <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
 Bajos A 08174, Sant Cugat del Valles,
 Barcelona, Spain
 Phone: +34 (93) 590 26 70
 Fax: +34 (93) 589 04 46
 E-mail: icom@icomspain.com
 URL: <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
 Kent, CT6 8LD, U.K.
 Phone: +44 (01227) 741741
 Fax: +44 (01227) 741742
 E-mail: info@icomuk.co.uk
 URL: <http://www.icomuk.co.uk>

Icom France s.a.s.

Zac de la Plaine,
 1 Rue Brindejonc des Moulinais, BP 45804,
 31505 Toulouse Cedex 5, France
 Phone: +33 (5) 61 36 03 03
 Fax: +33 (5) 61 36 03 00
 E-mail: icom@icom-france.com
 URL: <http://www.icom-france.com>

Icom Polska

81-850 Sopot, ul. 3 Maja 54, Poland
 Phone: +48 (58) 550 7135
 Fax: +48 (58) 551 0484
 E-mail: icompolska@icompolska.com.pl
 URL: <http://www.icompolska.com.pl>

Asia Icom Inc.

6F No. 88, Sec. 1 Cheng-Teh Road,
 Taipei, Taiwan, R.O.C.
 Phone: +886 (02) 2559 1899
 Fax: +886 (02) 2559 1874
 E-mail: sales@asia-icom.com
 URL: <http://www.asia-icom.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88, Yong Ding
 Road, Haidian District, Beijing, 100039, China
 Phone: +86 (010) 5889 5391/5392/5393
 Fax: +86 (010) 5889 5395
 E-mail: bjicom@bjicom.com
 URL: <http://www.bjicom.com>

Your local distributor/dealer: